VECTOROPTICS

XASR-3012 X-Accu 30mm 1.4" High Profile One Piece Picatinny Mount







Features

- 30mm Dia., 0MOA Type, Fit Max 56-60mm Scope Objective Lens, Six Screws Per Ring
- 35mm 1.4in Bottom to Ring Center, Extremely Accurate w/ Full CNC Machined
- Hard Anodizing, 21mm Picatinny Mount w/ 3 Crossing Bolts & Anti-Retreat Rings
- Can Accept Max 45 Inch / Pounds Torque Force for Big Nuts When Installing the Mount on the Picatinny Rail

VECTOR OPTICS

Specifications

XASR-3012



Diameter: 30mm

Overall Length: 154m / 6.1in Overall Height: 59mm / 2.3in Mount Length: 154mm / 6.1in Ring Width: 45.5mm / 1.8in

Central Height: 35mm / 1.4in, bottom to center

Ring Length: 26mm / 1.0in Gap Length: 70mm / 2.8in

Material: 6061-T6 aluminum alloy

Weight: 240g / 8.5oz Mount: Picatinny

Finish: Hard anodizing in black matte

Screws per ring: 6

High-durability aluminum alloy in black matte, designed for big recoil calibers

Do not use over 18 inch / pounds of torque on the scope rings' screws

Suggest 25 inch / pounds (Can Accept Max 45 Inch / Pounds) torque force for big nuts when installing the mount on the picatinny rail

Designed for hard and rigorous use

With T15 torx wrench and retail package, hex key can be used to fasten the clamp nuts